



图示(Pic. shown) : TLB-900-2P

General:	Terminal Strip	Rated : 750V,57A , 10mm ²
	18.50mm pitch , 02 Pole	
	Wire-to-Wire Connection	
	Screw clamp unit: M4, 1.2Nm Max	

认证 (Approval) :

技术参数 Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	600V	--	600V	--	750V	--
额定电流(Rated current)	50A	--	5A	--	57A	--
额定连接容量(Rated connection capacity)	18-8AWG Sol&Str			2.5~10mm ² Sol&Str, 16mm ² Sol Max		
绝缘材料(Insulation Material)				Ceramic		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Ni plated		
接线弹片材料(Material of Clamp spring)				--		
绝缘电阻(Insulation Resistance)				500MΩ or more at DC500V		
耐电压(1分钟)(Withstanding Voltage/1Min)				2500V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M4 , 1.2Nm Max		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				9.0mm		
使用温度(Operating temperature)				-40°C up to +200°C		
焊接方式(Soldering recommend)				--		

订购方式(How to order)

