



PCB terminal block — TLM series (Screwless Type) — TLM-210B



■ 图示(Pic. shown) : TLM-210B-05P-M17

General: PCB terminal block Rated : 320V,12A 1.5mm²
Single row, 5.00mm pitch, 02-20 Pole
Wiring orientation:165°(wire-to-board)
Screwless Type

认证 (Approval) :

■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	320V	--
额定电流(Rated current)	10A	--	10A	--	12A	--
额定连接容量(Rated connection capacity)	22AWG ~ 14AWG			0.25mm² ~ 1.5mm²		
刚性导线横截面 (AWG) (Conductor cross section,solid)				22~14		
柔性导线横截面 (AWG) (Conductor cross section,stranded)				22~14		
刚性导线横截面 (mm2) (Conductor cross section,rigid)				025~1.5		
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.25~1.5		
柔性导线横截面, 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic				0.25~1.0		
柔性导线横截面, 带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				0.25~1.0		
2根具有相同横截面的导线, 柔性, 带TWIN套管及塑料套管(mm2) (2 conductors with the same section flexible with TWIN ferrule and plastic sleeve)				/		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
绝缘材料组别(Material group)				I		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				Stainless Steel (GrNi)		
耐电压(1分钟)(Withstanding Voltage/1Min)				1600V		
额定冲击电压(Rated surge voltage)				4.0KV		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				--		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				9.0~10.0mm		
使用温度(Operating temperature)				-40℃ up to +115℃		
存储温度(Storage temperature)				-40℃ up to +70℃		
存储相对湿度(Storage relative humidity)				≤70%		
焊接方式(Soldering recommend)	Wave soldering ,260℃ 5S Max (Single Wave) , 260℃ 10S Max(Double Wave)					

■ 订购方式(How to order)

