


■ 图示(Pic. shown) : TL007P-08P-K

General. PCB terminal block Rated :300V,10A
Single row , 3.50mm pitch , 02P-24P Pole
Wiring orientation: 90°(wire-to-board)
Screw clamp unit: --

认证 (Approval) :



技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	--	--
额定电流(Rated current)	10A	--	10A	--	--	--
额定连接容量(Rated connection capacity)	--			--		
刚性导线横截面 (AWG) (Conductor cross section,solid)				--		
柔性导线横截面 (AWG) (Conductor cross section,stranded)				--		
刚性导线横截面 (mm2) (Conductor cross section,rigid)				--		
柔性导线横截面 (mm2) (Conductor cross section,flexible)				--		
柔性导线横截面 , 不带绝缘套管的冷压头(mm2) (Conductor cross section flexible , with ferrule without plastic				--		
柔性导线横截面 , 带绝缘套管的冷压头 (mm2) (Conductor cross section flexible , with ferrule with plastic sleeve)				--		
2根具有相同横截面的导线 , 柔性 , 带TWIN套管及塑料套管 (mm2) (2 conductors with the same section flexible with TWIN ferrule				--		
绝缘材料(Insulation Material)				PA66 UL94 V-0		
绝缘材料组别(Material group)				I		
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)				--		
耐电压(1分钟)(Withstanding Voltage/1Min)				1600V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				--		
固定螺丝(Mounting Screw) , 扭矩(torque)				--		
剥线长度(Wire stripping length)				--		
使用温度(Operating temperature)				-40°C up to +120°C		
存储温度(Storage temperature)				-40°C up to +70°C		
存储相对湿度(Storage relative humidity)				≤70%		
焊接方式(Soldering recommend)				Wave soldering ,260°C 8S Max		

■ 订购方式(How to order)

TL	0	07	P	—	XXXX	—	XXP	—	X
Series No. 系列号	Pitch间距 0=3.50mm	Differentiate Number 区分号	Pin header 插针		Special code 特编号 XXXX=custom-made blank=standard		No. of Poles 极数 02-24P		Color 颜色 Black:K

■ 插头 (Female Connector) — single row

P/N : TL006T

Orientation :

90° (plug-in to board)

Rated : 300V,10A

Screw clamp unit: M2.0, 0.2-0.25Nm