




PCB terminal block — BARRIER SERIES—B120C



■ 图示(Pic. shown) : B120C-04P-KC

General. PCB terminal block Rated : 300V,50A
Single row , 12.0mm pitch , 02-20 Pole
Screw clamp unit: M4,1.2N.m

认证 (Approval) :

■ 技术参数Technical Data	UL standard			IEC standard		
UL应用组别(UL Application group)	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	--	/	/	/
额定电流(Rated current)	50A	--	--	/	/	/
额定连接容量(Rated connection capacity)	22~8AWG			--		
刚性导线横截面 (AWG) (Conductor cross section,solid)	22~8			22~8		
柔性导线横截面 (AWG) (Conductor cross section,stranded)	22~8			22~8		
刚性导线横截面 (mm2) (Conductor cross section,rigid)	--			--		
柔性导线横截面 (mm2) (Conductor cross section,flexible)	--			--		
绝缘材料(Insulation Material)	PBT UL94V-0			PBT UL94V-0		
绝缘材料组别(Material group)	--			--		
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Ni plated			Copper alloy , Ni plated		
接线弹片材料(Material of Clamp spring)	--			--		
耐电压(1分钟)(Withstanding Voltage/1Min)	1600V			1600V		
额定冲击电压(Rated surge voltage)	--			--		
接线螺丝(Wire clamp unit Screw) , 最小扭矩(torque Max.)	M4 , 1.2 N·m			M4 , 1.2 N·m		
固定螺丝(Mounting Screw) , 扭矩(torque)	--			--		
剥线长度(Wire stripping length)	12 ~ 13mm			12 ~ 13mm		
使用温度(Operating temperature)	-40°C up to +120°C			-40°C up to +120°C		
存储温度(Storage temperature)	-40°C up to +70°C			-40°C up to +70°C		
存储相对湿度(Storage relative humidity)	≤70%			≤70%		
焊接方式(Soldering recommend)	--			--		

■ 订购方式(How to order)

