



PCB terminal block — BARRIER SERIES—B762-01-0773


 图示(Pic. shown) : B762-01-0773-06P-KC

General.

PCB terminal block Rated : 300V, 15A , 1.5mm²
 Single row , 7.62mm pitch , 02-34 Pole
 Wiring Connection : 180°(wire to board)
 Screw clamp unit: M3 , 0.5 ~ 0.8N·m

认证 (Approval) :



■ 技术参数Technical Data		UL standard			IEC standard		
UL应用组别(UL Application group)		UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)		300V	--	300V	/	450V	/
额定电流(Rated current)		15A	--	10A	/	17.5A	/
额定连接容量(Rated connection capacity)		22~14AWG			0.5~1.5mm ²		
刚性导线横截面 (AWG) (Conductor cross section,solid)				22~14			
柔性导线横截面 (AWG) (Conductor cross section,stranded)				22~14			
刚性导线横截面 (mm2) (Conductor cross section,rigid)				0.5~1.5			
柔性导线横截面 (mm2) (Conductor cross section,flexible)				0.5~1.5			
绝缘材料(Insulation Material)				PA66 UL94V-0			
绝缘材料组别(Material group)				/			
电流承载部件材料和镀层(Material & Plating of Current carrier)				Copper alloy , Tin plated			
接线弹片材料(Material of Clamp spring)				--			
耐电压(1分钟)(Withstanding Voltage/1Min)				2000V			
额定冲击电压(Rated surge voltage)				/			
接线螺丝(Wire clamp unit Screw) , 最大扭矩(torque Max.)				M3 , 0.5 ~ 0.8N·m			
固定螺丝(Mounting Screw) , 扭矩(torque)				--			
剥线长度(Wire stripping length)				7.5 ~ 8.5mm			
使用温度(Operating temperature)				-40℃ up to +105℃			
存储温度(Storage temperature)				-40℃ up to +70℃			
存储相对湿度(Storage relative humidity)				≤70%			
焊接方式(Soldering recommend)		Wave soldering ,260℃ 8S Max					

 订购方式(How to order)

B	762	—	01	—	XXXX	—	XXP	—	K	C
Series No. 系列号	Pitch间距 P=7.62mm		Solder Pin Spec 焊针规格		Special code 特编号 XXXX=custom-made 0773=standard		No. of Poles 极数 02-34P		Color 颜色 K=Black	Screw Type 螺丝 C=Cross