



PCB terminal block — BARRIER SERIES—B762CW-03


 图示(Pic. shown) : B762CW-03-05P-KC

General. PCB terminal block Rated : 300V, 15A
Single row, 7.62mm pitch, 02-32 Pole
Wiring Connection : 180°(wire to board)
Screw clamp unit: M3, 0.5 ~ 0.8N·m

认证 (Approval) :


 技术参数Technical Data

UL应用组别(UL Application group)	UL standard			IEC standard		
	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)	B	C	D	III / 3	III / 2	II / 2
额定电压(Rated voltage)	300V	--	300V	--	--	--
额定电流(Rated current)	15A	--	10A	--	--	--
额定连接容量(Rated connection capacity)	22~14AWG			--		
刚性导线横截面 (AWG) (Conductor cross section,solid)	22~14			22~14		
柔性导线横截面 (AWG) (Conductor cross section,stranded)	22~14			22~14		
刚性导线横截面 (mm ²) (Conductor cross section,rigid)	--			--		
柔性导线横截面 (mm ²) (Conductor cross section,flexible)	--			--		
绝缘材料(Insulation Material)	PA66 UL94V-0			PA66 UL94V-0		
绝缘材料组别(Material group)	/			/		
电流承载部件材料和镀层(Material & Plating of Current carrier)	Copper alloy , Tin plated			Copper alloy , Tin plated		
接线弹片材料(Material of Clamp spring)	--			--		
耐电压(1分钟)(Withstanding Voltage/1Min)	2000V			2000V		
额定冲击电压(Rated surge voltage)	/			/		
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.)	M3, 0.5 ~ 0.8N·m			M3, 0.5 ~ 0.8N·m		
固定螺丝(Mounting Screw), 扭矩(torque)	--			--		
剥线长度(Wire stripping length)	7 ~ 8mm			7 ~ 8mm		
使用温度(Operating temperature)	-40°C up to +120°C			-40°C up to +120°C		
存储温度(Storage temperature)	-40°C up to +70°C			-40°C up to +70°C		
存储相对湿度(Storage relative humidity)	≤70%			≤70%		
焊接方式(Soldering recommend)	Wave soldering ,260°C 8S Max			Wave soldering ,260°C 8S Max		

 订购方式(How to order)

B	762	C	W	—	03	—	XXXX	—	XXP	—	X	C
Series No. 系列号	Pitch间距 P=7.62mm	With Cover C=Cover	With flange 带法兰		Solder Pin Spec 焊针规格		Special code 特编号 XXXX=custom-made blank=standard		No. of Poles 极数 02-32P		Color 颜色 Black : K	Screw Type 螺丝 C : Cross